



Tel: 011 741 5600 | info@hrp.co.za | www.harveyroofingproducts.co.za / www.macsteel.co.za

HARVEYTHATCH

INSTALLATION SPECIFICATION FOR RE-ROOFING AND NEW ROOFS

NOTE:

- A. In order to comply to the A-Class Fire rating as tested in accordance to SANS 1077 – part 12 (CSIR), Harvey Thatch Tiles has to be installed in accordance to our prescribed installation specification
- B. Harvey Roofing Products will only issue a product warranty subject to:
 - Installation done by a trained Harvey Roofing installer
 - Installation has been executed in accordance to the specification, i.e:

PRODUCT	SPECIFICATION
Timber truss / support frame / 'gum poles'	Micon Coating: Pacsyf™ treated
Thatch grass layer / Cape Reed	Inside as well as outside to be treated with Micon coatings: Thatchsayf™
Pink Aerolite 50mm	Ensure all ridges, eaves and bottom edges are covered with Pink Aerolite. Do not use as 'fill' - has to cover the battens
Harvey Thatch Tile coated with natural stone	Galvanised substrate for inland application (10km plus) and zinc-aluminium substrate for coastal application (not suitable for proximity closer than 1km from breaking surf)

Harvey Roofing Products shall not be responsible in any way whatsoever for the actions of incorrect installations and/or workmanship

